



**Table 16 Engineering Data**

UBC Model No.*	R-717 Tons*	Fans		Weights			Refrigerant Operating Charge lbs.***	Coil Volume ft <sup>3</sup>	Spray Pump		Remote Pump			Dimensions				
		HP	CFM	Shipping	Operating	Heaviest Section†			HP	GPM	Gallons Req'd**	Conn. Size	Operating Weight	Height H	Upper U	Lower E	Coil A	Length L
1090	773	(2)25	243,000	42,310	59,500	15,500	905	123	(2) 7-1/2	2,400	1,440	(2)12"	51,260	15' 2-5/8"	8' 2-1/2"	7' 1/8"	22-1/4"	18' 0"
1240	879	(2)20	231,900	49,160	66,940	18,610	1,190	163	(2) 7-1/2	2,400	1,440	(2)12"	58,700	15' 11-1/8"	8' 11"	7' 1/8"	30-3/4"	18' 0"
1310	929	(2)25	239,000	49,320	67,100	18,690	1,190	163	(2) 7-1/2	2,400	1,440	(2)12"	58,860	15' 11-1/8"	8' 11"	7' 1/8"	30-3/4"	18' 0"
1370	972	(2)30	248,300	49,560	67,340	18,810	1,190	163	(2) 7-1/2	2,400	1,440	(2)12"	59,100	15' 11-1/8"	8' 11"	7' 1/8"	30-3/4"	18' 0"
1435	1018	(2)25	230,000	55,980	74,490	21,760	1,485	202	(2) 7-1/2	2,400	1,440	(2)12"	66,250	16' 7-5/8"	9' 7-1/2"	7' 1/8"	39-1/4"	18' 0"
1500	1064	(2)30	239,600	56,220	74,730	21,880	1,485	202	(2) 7-1/2	2,400	1,440	(2)12"	66,490	16' 7-5/8"	9' 7-1/2"	7' 1/8"	39-1/4"	18' 0"
1575	1117	(2)40	256,700	56,780	75,290	22,160	1,485	202	(2) 7-1/2	2,400	1,440	(2)12"	67,050	16' 7-5/8"	9' 7-1/2"	7' 1/8"	39-1/4"	18' 0"
1625	1152	(2)40	249,500	63,560	82,800	25,230	1,770	241	(2) 7-1/2	2,400	1,440	(2)12"	74,560	17' 4-1/8"	10' 4"	7' 1/8"	47-3/4"	18' 0"