



# Model 3196 STX

## 60 Hz Performance Curve

**725.1C2**  
 October 20, 2000  
 (Sup. 7/11/97)

**Size: 1 x 1½-6      Group: STX      RPM: 3500**

### Commercial Data

Customer \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 F.O. No. \_\_\_\_\_  
 P.O. No. \_\_\_\_\_  
 Item No. \_\_\_\_\_  
 Equip. No. \_\_\_\_\_  
 Service \_\_\_\_\_  
 \_\_\_\_\_  
 Date \_\_\_\_\_  
 Certified By \_\_\_\_\_  
 \_\_\_\_\_

### Technical Data

Liquid \_\_\_\_\_  
 Temp. \_\_\_\_\_ S.G. \_\_\_\_\_ Visc. \_\_\_\_\_  
 Max. Diameter Solids .344 in. (8.7mm)  
 Flow \_\_\_\_\_ TDH \_\_\_\_\_  
 NPSH<sub>A</sub> \_\_\_\_\_ NPSH<sub>R</sub> \_\_\_\_\_  
 Pump Minimum Flow \_\_\_\_\_  
 Impeller Diameter \_\_\_\_\_  
 Pump Power \_\_\_\_\_  
 Power Consumption  
 Mech. Seal/Dyn Seal \_\_\_\_\_  
 Other Power Losses \_\_\_\_\_  
 Rated Hydraulic Efficiency \_\_\_\_\_  
 \_\_\_\_\_

